

## 1000 W VHF/FM Transmitter T3273



### Highlights of the VHF/FM Transmitter T3273

- Simple and intuitive menu control via graphic display
- Service friendly design with plug-in Eurocard modules
- 19" slide-in technology of height 9 U
- All important functions and status information of the transmitter are simultaneously shown on the graphic display
- Prepared for all reserve concepts
- Directly modulated synthesizer with 10 kHz channel separation
- Integrated stereo encoder with deviation limiter
- Proven MOSFET technology of the power transistors
- Excellent reliability due to low junction temperatures of <math>90^{\circ}\text{C}</math> at T (ambient) = <math>25^{\circ}\text{C}</math>
- Very good quality data in with respect to unweighted- and weighted S/N ratio, stereo cross-talk, frequency response and non-linear distortion
- Protective circuits against overvoltage, fan failure, overtemperature and mismatch
- RF output power continuously adjustable between 200 W and 1000 W in 1 W steps
- The output is delivered by four 250 W amplifiers, connected in parallel by three 2:1 combiners.
- Each 250 W amplifier is equipped with a harmonic filter

### Technical Data

RF output connector  
 Remote interfaces

Operating mode (freely selectable)  
 Number of preset frequencies  
 AF patching for the left- and right channel  
 Level controller for 40 kHz deviation  
 Setting accuracy  
 Pilot tone level adjustable  
 RDS input level adjustable  
 SCA input level adjustable  
 Preemphasis (on/off switchable)  
 Cooling  
 Operational in the temperature range  
 Humidity  
 Dimensions W x H x D in mm  
 Weight

N, 50  $\Omega$   
 Standard: RS232  
 Option: Relay, BITBUS, SNMP or HTTP  
 Mono, stereo, MPX, (L+R)/2  
 6  
 Option, LEMO-Triaxial  
 - 5.25 dBm ... + 12.5 dBm, in 0.25 dB steps  
 $\leq 0.1$  dB  
 - 25 dBu ... - 5 dBu  
 - 23 dBu ... - 9.5 dBu  
 - 23 dBu ... - 9.5 dBu  
 25, 50, 75  $\mu\text{sec}$   
 Internal fan  
 -  $10^{\circ}\text{C}$  ... +  $50^{\circ}\text{C}$   
 to 95 %, without dew  
 483 x 396 x 370  
 31 kg

The VHF/FM transmitter fulfils the national standards as well as the technical specifications of the ARD (5/ 3.1), the Deutschen Telekom (TS 0216) and ETSI EN 302 018-2.

**Transmitter Power**

Output power $P_{RF}$	1000 W
Amplifiers	4 * 250 W
Output power setting range	200 W ... 1000 W, continuous
Full power up to VSWR = 1.5	thereafter down regulation of output power

**Frequency**

Frequency range	87.5 MHz ... 108 MHz, in 10 kHz steps
Frequency change	< 1 sec
Frequency drift over 3 months	< 300 Hz
Setting accuracy	< 50 Hz
Middle frequency shift during modulation	0 Hz
Deviation instability	< 1 %
Warm-up time	< 5 min

**Out-of-band Emission**

0.2 MHz	< - 110 dBc/Hz
0.3 MHz	< - 126 dBc/Hz

**Spurious Emission**

Harmonic emissions	< - 80 dBc
Noise power density	< - 150 dBc/Hz

**Reverse Intermodulation Products**

	> 15 dB
<b>Input Impedance</b>	> 2000 $\Omega$ or 600 $\Omega$

**Linear Distortion**

Stereo cross-talk attenuation	
40 Hz ... 15 kHz	> 45 dB
Amplitude deviation	
40 Hz ... 65 kHz	$\pm$ 0.1 dB
> 65 kHz ... 76 kHz	$\pm$ 0.2 dB
100 kHz	- 2 dB $\pm$ 0.5 dB
Damping of the 15 kHz low-pass	
40 Hz ... 15 kHz	< 0.2 dB
at 19 kHz	> 50 dB

**Non-Linear Distortion**

Distortion factor 40 Hz ... 15 kHz, at 75 kHz deviation	< 0.1 % = - 60 dB
---	-------------------

**Selective S/N Ratio**

Mono	> 80 dB
Stereo	> 80 dB

**Unweighted S/N Ratio (effective peak value)**

Mono	> 72 dB
Stereo	> 72 dB
AM unweighted S/N ratio, asynchronous	> 60 dB
AM unweighted S/N ratio, synchronous	> 60 dB

**Weighted S/N Ratio (effective peak value)**

Mono	> 70 dB
Stereo	> 70 dB
AM weighted S/N ratio, asynchronous	> 60 dB

**Power Supply**

Voltage range	1/N/PE 115 V	95 V ... 132 V
	1/N/PE 230 V	195 V ... 264 V
Mains frequency		47 Hz ... 63 Hz
Power consumption		2200 W at $P_{RF} = 1000$ W
$\cos \varphi$		> 0.7
Ready after mains failure		< 2 sec

**Contact address:**

TRANSRADIO SenderSysteme Berlin AG  
 Mertensstr. 63,  
 13587 Berlin, Germany  
 Telephone: ++49-30-339 78-0  
 Telefax: ++49-30-339 78-599  
 Email: [info@tsb-ag.de](mailto:info@tsb-ag.de)  
 Internet: <http://www.transradio.de>